# Calculus O

Operating Instructions







#### **Seat Height**

Lift right hand lever. Use body weight to raise or lower the seat (sit on the seat to move down, take weight off to move up). The seat will lock at the height the lever is released.





#### **Freefloat Mechanism**

Pull up rear lever to right and side of seat. The chair back will remain in permanent contact with the user as they move throughout the day. To secure the back at any desired angle push lever down.





### **Back Height**

Place hand below back and slowly lift to desired height using 8-point ratchet system. When the highest point is reached the back will drop to the starting position.





#### Height Adjustable Arm

Pull up button on the inside of the arm to raise or lower. Release when at desired position.

Please note all instructions are assuming the user is sat in the chair.

**broadstock** 

# Calculus •

Operating Instructions



Please note all instructions are assuming the user is sat in the chair.

### Optional Extras



#### **Independent Seat Tilt**

Lift forward lever on the left hand side of the seat to tilt forward. Release to lock in position.



### 8

#### **Pump-up Lumbar Support**

Repeatedly press rubber air cell located to the left until the lumbar has reached the required firmness. To deflate, press the button on the top of the air cell.



#### **Synchronous Movement**

Pull up rear lever to the right hand side of the seat. The seat and back will move together in a ratio of 2.5:1. To secure in any desired position push down lever. To adjust the tension to the weight of the user, adjust the rear knob situated under the front of the seat, turn clockwise to increase resistance and anti-clockwise to decrease.



#### **Pronounced Lumbar Roll**

This is a fixed lumbar cushion which can only be fitted into the chair at the time of manufacture. It is not adjustable.



#### **Seat Slide**

Lift lever located on the left under the seat and use weight to move seat forward. There should be up to 3 fingers gap between the front of the seat and behind your knees when sat all the way back in the chair.



# Extra Height Gas Spindle & Footring

This base may be fitted to the chair for counter or bench work. The footring is independently adjustable to suit the user. All chairs fitted with this option are supplied with glides instead of castors.

